



G-Smooth (US)

G-Smooth is a paradox. It is a woodfree, coated matt paper for demanding image reproduction, yet with significant bulk and stiffness - and a low-reflecting surface which guarantees good readability. G-Smooth has a smooth surface for reproduction of high-resolution photographs. Opacity, bulk and stiffness are very high compared to othersilk and matt papers. It also has a rich paper feel, outstanding runnability and post-treatment properties. G-Smooth is ideal for art books, covers, luxury magazines, Direct Mail, brochures, catalogues, folders, posters, inserts and cards. G-Smooth is available both as sheets and reels in various sizes in grammages from 90 to 250 g/m².

G-Smooth standard products are available as FSC® – The mark of responsible forestry. www.fsc.org. FSC-C007342 and PEFC™ PEFC/05-33-98 certified



Technical specifications

| | |
|---------------------------------|---|
| Basic information: | Optimized for colour printing, Available in sheets, Available in reels |
| Surface: | Coated, Semi-matt |
| Shade: | White |
| Printing techniques: | Offset (heatset), Offset (sheet-fed), Flexo, Laser, HP Indigo |
| Certificates/Statements: | FSC_C007342, PEFC_053398, The paper is inspected for Nordic Ecolabelled printing , ECF, ISO 14001, EMAS, Paper Profile, Safety of Toys, Food contact, Woodfree, Cradle to Cradle Certified® |

G-Smooth

| | | | | | | | | |
|-----------------------------------|----|-----|-----|-----|-----|-----|-----|-----|
| Grammage (g/m²) | 90 | 100 | 115 | 130 | 150 | 170 | 200 | 250 |
|-----------------------------------|----|-----|-----|-----|-----|-----|-----|-----|

| | | | | | | | | |
|--------------------------------------|-----|-------|-------|-----|--------|--|--|--|
| Basis Weight (Text 25x38) Lbs | 61T | 67.5T | 77.5T | 88T | 101.5T | | | |
|--------------------------------------|-----|-------|-------|-----|--------|--|--|--|

| | | | | | | | | |
|---------------------------------------|--|--|--|--|--|-----|-----|-------|
| Basis Weight (Cover 20x26) Lbs | | | | | | 63C | 74C | 92.5C |
|---------------------------------------|--|--|--|--|--|-----|-----|-------|

| | | | | | | | | |
|----------------|-----|-----|-----|-----|-----|-----|-----|------|
| Caliper | 3.2 | 3.6 | 4.2 | 4.9 | 5.7 | 6.5 | 8.0 | 10.0 |
|----------------|-----|-----|-----|-----|-----|-----|-----|------|

| | | | | | | | | |
|--------------------|----|------|----|----|----|----|----|------|
| Opacity (%) | 92 | 94.5 | 96 | 97 | 98 | 98 | 99 | 99.5 |
|--------------------|----|------|----|----|----|----|----|------|

| | | | | | | | | |
|-----------------------------|------|------|------|------|------|------|------|------|
| Brightness (Tappi %) | 90.5 | 90.5 | 90.5 | 90.5 | 90.5 | 90.5 | 90.5 | 90.5 |
|-----------------------------|------|------|------|------|------|------|------|------|

| | | | | | | | | |
|--|----|----|----|----|----|----|----|----|
| Smoothness (Tappi, Sheffield units) | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 |
|--|----|----|----|----|----|----|----|----|

Values are targets only and can be subject to changes over time without prior notice. You will find the latest technical information and other technical recommendations about our products at arcticpaper.com

Screen recommended, max 175 lpi