

Munken Lynx

Extraordinary printing demands extraordinary design paper. The uncoated smooth surface of Munken Lynx and its natural white shade make images genuine and gives an exclusive and yet very true natural paper feel. Munken Lynx is developed for offset print, but is also suitable for various kinds of printing techniques; flexo, laser, xerography, digital printing, inkjet and for preprint applications. Also available is a cream shade, Munken Pure, a crispy white version, Munken Polar and the highwhite Munken Kristall.

Munken Lynx standard products are available as EU Ecolabel, FSC® – The mark of responsible forestry. www.fsc.org. FSC-C020637 and PEFC™ PEFC/05-33-99 certified.



The mark of
responsible forestry



EU Ecolabel : SE/011/05



Technical specifications

Basic information:	Optimized for colour printing, Available in sheets, Available in reels
Surface:	Smooth, Uncoated
Shade:	White
Printing techniques:	Offset, Flexo, Laser, Inkjet (black/white)
Certificates/Statements:	FSC_C020637, PEFC_053399, EU Ecolabel, The paper is inspected for Nordic Ecolabelled printing , ECF, ISO 14001, EMAS, Paper Profile, Safety of Toys, Food contact, Age resistant (ISO 9706), Woodfree, Cradle to Cradle Certified®

Munken Lynx

Grammage (g/m²)	70 ^D	80*	90*	100	120	130	150	170	200	240	-	400 ^B	600 ^B
Opacity (%)	86	89	91	93	95	96	97	98	99	99	-	100	100
Thickness (µm)	79	104	117	113	136	147	170	192	226	271	-	452	678
Bulk (thickness/grammage)	1.13	1.3	1.3	1.13	1.13	1.13	1.13	1.13	1.13	1.13	-	1.13	1.13
Whiteness (CIE)	116	116	116	116	116	116	116	116	116	116	-	116	116
Brightness (ISO 2470/D65 %)	96	96	96	96	96	96	96	96	96	96	-	96	96
Roughness (Bendtsen, ml/min)	150	150	150	150	150	150	150	150	150	150	-	150	150
Ytvikt (g/m²)	-	-	-	-	-	-	-	-	-	-	300	-	-
Opacitet (%)	-	-	-	-	-	-	-	-	-	-	100	-	-
Tjocklek (µm)	-	-	-	-	-	-	-	-	-	-	339	-	-
Bulk (tjocklek/ytvikt)	-	-	-	-	-	-	-	-	-	-	1.13	-	-
Vithet (CIE)	-	-	-	-	-	-	-	-	-	-	116	-	-
Ljushet (ISO 2470/D65 %)	-	-	-	-	-	-	-	-	-	-	96	-	-
Ytråhet (Bendtsen, ml/min)	-	-	-	-	-	-	-	-	-	-	150	-	-

^B Laminated paper

^D Not standard production. Min. 10 tonnes and paper machine trim needed.

* Fully preprint adapted

Screen recommended 133-150 lpi

Values are targets only and can be subject to changes over time without prior notice. You will find the latest technical information and other technical recommendations about our products at arcticpaper.com