

# Munken Lynx (US)

Extraordinary printing demands extraordinary design paper. The uncoated smooth surface of Munken Lynx and its natural white shade make images genuine and gives an exclusive and yet very authentic appeal. Munken Lynx is developed for offset print, but is also suitable for various kinds of printing techniques; flexo, laser, xerography, digital printing, inkjet and for preprint applications. 80 & 90 g/m<sup>2</sup> / 54T & 61T lbs. are even further developed as fully adapted preprint paper. Also available is a cream white shade, Munken Pure, a bright white version, Munken Polar and the high white Munken Kristall.

Munken Lynx standard products are available as EU Ecolabel, FSC® FSCC020637 and PEFC™ PEFC/05-33-99 certified.



The mark of  
responsible forestry



EU Ecolabel : SE/011/05



**BRONZE**

## Technical specifications

<b>Basic information:</b>	Optimized for colour printing, Available in sheets, Available in reels
<b>Surface:</b>	Uncoated, Smooth
<b>Shade:</b>	White
<b>Printing techniques:</b>	Offset, Flexo, Laser, Inkjet (black/white)
<b>Certificates/Statements:</b>	FSC_C020637, PEFC_053399, EU Ecolabel, The paper is inspected for Nordic Ecolabelled printing , ECF, ISO 14001, EMAS, Paper Profile, Safety of Toys, Food contact, Age resistant (ISO 9706), Woodfree, Cradle to Cradle Certified®

# Munken Lynx

<b>Grammage (g/m<sup>2</sup>)</b>	80*	90*	100	120	130	150	170	200	240	300 <sup>B</sup>	400 <sup>B</sup>	600 <sup>B</sup>
-----------------------------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	------------------	------------------	------------------

<b>Basis Weight (Text 25x38) Lbs</b>	54T	61T	67.5T	81T	88T	101.5T
--------------------------------------	-----	-----	-------	-----	-----	--------

<b>Basis Weight (Cover 20x26) Lbs</b>							63C	74C	89C	111C	148DT	222DTC
---------------------------------------	--	--	--	--	--	--	-----	-----	-----	------	-------	--------

<b>Opacity (%)</b>	89	91	93	95	96	97	98	99	99	100	100	100
--------------------	----	----	----	----	----	----	----	----	----	-----	-----	-----

<b>Caliper</b>	4.1	4.6	4.5	5.3	5.8	6.7	7.6	8.9	10.7	13.3	17.8	26.7
----------------	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------

<b>Brightness (Tappi %)</b>	88	88	88	88	88	88	88	88	88	88	88	88
-----------------------------	----	----	----	----	----	----	----	----	----	----	----	----

<b>Smoothness (Tappi, Sheffield units)</b>	120	120	120	120	120	120	120	120	120	120	120	120
--	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

<sup>B</sup> Laminated paper

<sup>D</sup> Not standard production. Min. 10 tonnes and paper machine trim needed.

\* Fully preprint adapted

Screen recommended 133-150 lpi

Values are targets only and can be subject to changes over time without prior notice. You will find the latest technical information and other technical recommendations about our products at [arcticpaper.com](http://arcticpaper.com)