



PRODUCT G-Smooth

COMPANY Arctic Paper S.A.

MILL Arctic Paper Grycksbo AB

Information gathered from 2021-01-01 to 2021-12-31 Date of issue 2022-03-28

ENVIRONMENTAL PRODUCT DECLARATION FOR PAPER

ENVIRONMENTAL MANAGEMENT

Certified environmental management system at the mill: ISO 14001 and EMAS-registration since 1997

Company systems ensure traceability of the origin of wood: YES NO 100% RECOVERED PAPER

FSC® Chain of Custody License no. FSC-C007342

PEFC Chain of Custody License no. PEFC/05-33-98 Certificate no. 2008-SKM-PEFC-31

ENVIRONMENTAL PARAMETERS

The figures are based on methods and procedures of measurement approved by the local (or national) environmental regulators at the production site. The figures include pulp and paper production.

Water			
COD	5.3		kg/tonne
AOX	0.03		kg/tonne
NTot	0.09		kg/tonne
PTot	0.02		kg/tonne

Air			
SO ₂	0.06		kg/tonne
NO _x	0.84		kg/tonne
CO ₂ (fossil)	61		kg/tonne

Solid waste landfilled 10 BDkg/tonne


Purchased electricity consumption
/tonne of final product 663 kWh

MORE INFORMATION

Contact Pethra Nodlund

Address Arctic Paper Grycksbo AB, Box 1
SE 790 20 Grycksbo, Sweden

PRODUCT COMPOSITION



This product contains biomass carbon, equivalent to 972 kg of CO₂ per tonne of product.

Phone +46 72 241 87 81

e-mail pethra.nordlund@arcticpaper.com

Arctic Paper Grycksbo AB

Paper Mill Environmental Declaration

Product information: G-Smooth

Arctic Matt is a matt, coated paper with a soft, white surface with a natural feel. The paper has good opacity and rigidity, high bulk and excellent printing and finishing properties. The matt surface provides a reader-friendly, reflection-free surface.

The environmental data below reports only emissions from the paper production and not emission in the total production chain from forest to customers.

Mill Environmental Parameters 2021

		Product	BAT ¹	Description ²
Water	Quantity ³	7.3		m ³ /t
	COD	0.61	0.15-1.5	kg/t
	AOX	0.0009		kg/t
	N-tot	0.033	0.01-0.1	kg/t
	P-tot	0.0005	0.003-0.012	kg/t
Air	SO ₂	0		kg/t
	NO _x	0.13		kg/t
	CO ₂	0		kg/t
Energy	Steam	995		kWh/t
	Process	637		kWh/t
Waste	Reuse	10.9		BDkg/t
	Landfill	0.58		BDkg/t

¹ BAT = Best available technique according to EU 2014/687

² All figures expressed per ton of paper

³ Effluent water from wastewater treatment plant

Mill Environmental Objectives 2022

2% improvement of TOC as an 5-year average.

Strategic suppliers to have 70% fossil free transports by 2027

For more information about environmental objectives, see the EMAS environmental

Sales contact

Arctic Paper Grycksbo AB
Box 1
SE 790 20 Grycksbo, Sweden
Tel +46 10 451 80 39
Mob +46 70 560 67 04
jaana.ahlroos@arcticpaper.com
arcticpaper.com

Jaana Ahlroos

Mill contact

Arctic Paper Grycksbo AB
Box 1
SE 790 20 Grycksbo, Sweden
Tel +46 72 241 80 00
Mobil +46 72 241 87 81
pethra.nordlund@arcticpaper.com
arcticpaper.com

Pethra Nordlund

