

G-PRINT

G-Print is a woodfree coated paper. High bulk, generous paper feel and excellent runability, making G-Print a great paper choice. Smooth yet bulky it is noted for its consistent technical quality. The smooth, low-reflecting surface provides both perfect readability and quality image reproduction, with high gloss contrast. G-Print offers sharp, even print and low mottling tendencies. Finishing performance provides unique folding and binding properties. G-Print is ideal for books, magazines, brochures, catalogues, covers, direct mail, folders, posters, inserts and maps. G-Print is available both as sheets and reels in various sizes in grammages from 70 to 300 g/m².

G-Print standard products are available as FSC $^{\textcircled{8}}$ – The mark of responsible forestry. www.fsc.org. FSC-C007342 and PEFC TM PEFC/05-33-98 certified.

roducts are available as $\mathsf{FSC}^{ exttt{ iny B}}$ – The mark of responsible

BASIC INFORMATION

Optimized for colour printing. Available in sheets. Available in reels

CERTIFICATES / STATEMENTS

The paper is inspected for Nordic Ecolabelled printing, ECF, ISO 14001, EMAS, Paper Profile, Safety of Toys , Woodfree, Food contact, FSC_C007342, PEFC_053398

PRINTING TECHNIQUES

Offset (heatset), Offset (sheet-fed), Flexo, Laser, HP Indigo

SHADE

White

SURFACE

Coated, Matt





G-PRINT

| Grammage (g/m²) | 70 | 80 | 90 | 100 | 115 | 130 | 150 | 170 | 200 | 250 | 300 |
|--|------|------|------|------|------|------|-----|------|------|------|------|
| Opacity (%) | 87.5 | 90.5 | 92 | 93.5 | 96 | 97 | 98 | 98.5 | 99 | 99.5 | 99.5 |
| Thickness (µm) | 68 | 77 | 87 | 98 | 113 | 129 | 150 | 172 | 203 | 255 | 318 |
| Bulk (thickness/grammage) | 0.96 | 0.96 | 0.97 | 0.98 | 0.98 | 0.99 | 1.0 | 1.01 | 1.02 | 1.02 | 1.06 |
| Whiteness (CIE) | 117 | 117 | 117 | 117 | 117 | 117 | 117 | 117 | 119 | 119 | 119 |
| Brightness (ISO 2470/D65 %) | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 97 | 97 | 97 |
| Smoothness (PPS, µm) | 2.8 | 2.8 | 2.8 | 2.8 | 2.8 | 2.8 | 2.8 | 2.8 | 2.2 | 2.2 | 2.8 |
| Surface Gloss (TAPPI T 480: 75°, g.u.) | <25 | <25 | <25 | <25 | <25 | <25 | <25 | <25 | <30 | <30 | <30 |